

PIPE OD RANGE				QUICKLINKS	DOVETAIL QUICKLINK
MIN (in)	MAX (in)	MIN (mm)	MAX (mm)	EES004	EES011
4.0	5.2	102	132	0	1
5.2	6.6	132	168	1	
6.6	8.0	168	203	2	
7.9	9.3	201	236	3	
9.2	10.5	234	267	4	
10.4	11.7	264	297	5	
11.6	12.8	295	325	6	
12.7	14.0	323	356	7	
13.9	15.1	353	384	8	
15.0	16.2	381	411	9	
16.1	17.4	409	442	10	
17.2	18.6	437	472	11	
18.3	19.6	465	498	12	
19.4	20.6	493	523	13	
20.4	21.7	518	551	14	
21.5	22.8	546	579	15	
22.6	23.9	574	607	16	
23.7	24.9	602	632	17	
HIGH TEMPERATURE PIPE OD RANGE					HT QUICKLINK
MIN (in)	MAX (in)	MIN (mm)	MAX (mm)		CES109
4.0	5.2	102	132		1
5.2	6.6	132	168		2
6.6	8.0	168	203		3
7.9	9.3	201	236		4
9.2	10.5	234	267		5
10.4	11.7	264	297		6
11.6	12.8	295	325		7
12.7	14.0	323	356		8
13.9	15.1	353	384		9
15.0	16.2	381	411		10
16.1	17.4	409	442		11
17.2	18.6	437	472		12
18.3	19.6	465	498		13
19.4	20.6	493	523		14
20.4	21.7	518	551		15
21.5	22.8	546	579		16
22.6	23.9	574	607		17
23.7	24.9	602	632		18

■ ROTIX KEY PARTS

- | | |
|---|---------------------------|
| A | Slider PPS Encoder |
| B | Silder PPS |
| C | Encoded Skew Probe Holder |
| D | ROTIX - Low Profile Link |
| E | Dovetail QuickLink |
| F | Encoder Cable |
| G | Cable Management |
| H | QuickLink |
| I | QuickLink Buckle |

