

Features

Various Lengths

• Outfit the Pit Gage with 2 or 4 extension arms.

Rotating Face


• Pivot the display 360° to accommodate inverted pit measurement.

Stroke

• 25 mm (1 in) digital indicator range.

Magnetic Arms¹

• Magnetic arms allow the Pit Gage to be attached to ferrous surfaces.







Accessories

Extension Arm Kit

· Increase overall Pit Gage length to 103 cm (40.6 in) by adding 2 additional extension arms during large dent inspection.



Magnetic Arm Kit

• Arms with variable magnetic attraction provide ease of use during inverted inspection applications.



Kit Contents

Standard Kit Contents

- Digital Indicator
- Centre Base
- Blind Side Base
- Extension Arms
- Indicator Tip³
- Rugged Carrying Case
- User Manual



Additional Features

Small Diameter Inspection

· A small radius along the bottom of the gage accommodates small diameters.

Waterproof

Rated to IP67.

Warranty

 Three year warranty on all Jireh products.4








Weight and Dimensions

Shipping Weight

• 2 arm kit: 1.17 kg (2.6 lb)• 4 arm kit: 1.54 kg (3.4 lb)

Dimensions

- A: 17.6 cm (6.9 in) • B: 42 cm (16.6 in) • C: 5.8 cm (2.3 in)• D: 72.5 cm (28.6 in) • E: 15 cm (5.9 in) F: 9.5 cm (3.8 in)• G: 11.6 cm (4.6 in)



Environmental Specifications

Operating Environment

■ -10° C (14° F) to 50° C (122° F)

Environmental Sealing

Waterproof (IP67)

Specifications

Digital Indicator, Range

• 0 - 25 mm (0 - 1 in)

Digital Indicator, Resolution

• 0.01 mm (0.005 in)

Digital Indicator, Stem Diameter

• 9.52 mm (0.375 in)

Battery Requirements

2 - CR2032 lithium coin cells²

Inspection Surface

· Ferrous or non-ferrous materials