

PIPE OD RANGE				LINKS	
MIN (in)	MAX (in)	MIN (mm)	MAX (mm)	SHORT*	LONG
4.4	5.2	111	133	1	0
5.1	6.0	129	152	2	0
5.8	6.8	148	172	3	0
6.6	7.6	168	192	4	0
7.4	8.4	187	212	5	0
8.2	9.2	207	233	6	0
9.0	10.0	228	253	7	0
9.8	10.8	248	274	8	0
10.6	11.6	268	294	9	0
11.4	12.4	289	315	10	0
12.3	13.3	312	338	8	1
13.1	14.1	332	358	9	1
13.9	14.9	352	378	10	1
14.9	15.9	378	404	2	4
15.7	16.7	398	424	3	4
16.5	17.5	419	445	1	5
17.3	18.3	439	465	2	5
18.0	19.1	458	485	3	5
18.9	19.9	480	506	1	6
19.7	20.7	499	526	2	6
20.4	21.5	519	545	3	6
21.2	22.3	539	565	4	6
22.0	23.0	559	585	5	6
22.8	23.8	579	605	6	6
23.6	24.6	599	625	7	6
24.4	25.4	619	645	8	6
25.1	26.2	639	666	9	6
25.9	27.0	659	686	10	6
26.8	27.9	681	708	2	9
27.6	28.6	701	728	3	9
28.4	29.5	721	748	1	10
29.2	30.2	741	768	2	10
30.0	31.0	761	788	3	10
30.8	31.8	782	809	1	11
31.6	32.6	802	829	2	11
32.4	33.4	822	849	3	11
33.1	34.2	842	869	4	11
33.9	35.0	862	889	5	11
34.7	35.8	882	909	6	11
35.5	36.6	902	929	7	11
36.3	37.4	922	950	8	11
37.1	38.2	942	970	9	11
37.9	39.0	962	990	10	11

*Short includes: Short Link, Dovetail Link, Red Catch Link

FOUR PROBE WELD FRAME CHAIN SCANNER: Key Parts

A	Overhead Adjustable Link
B	Short Link
C	Dovetail Link
D	Catch Link
E	Long Link
F	Buckle
G	Probe Holder
H	Encoder

