

## SHORT LATCH REQUIRED

OUTER Ø RANGE				LINK TYPE				PIPE OD	TUBE OD
MIN (in)	MAX (in)	MIN (mm)	MAX (mm)	SHORT	MEDIUM	LONG	WHEEL	(in)	(in)
0.84	0.94	21	24	0	0	0	0	0.84	0.88
0.94	1.03	24	26	1	0	0	0		1.00
1.02	1.11	26	28	0	0	0	1	1.05	
1.11	1.20	28	30	1	0	0	1		1.13
1.20	1.28	30	33	0	0	0	2		
1.28	1.37	33	35	1	0	0	2	1.32	1.32
1.37	1.45	35	37	0	0	0	3		1.38
1.45	1.53	37	39	1	0	0	3		1.50
1.53	1.62	39	41	0	0	0	4		
1.61	1.70	41	43	1	0	0	4	1.66	
1.70	1.78	43	45	0	0	0	5		1.75
1.78	1.86	45	47	1	0	0	5		
1.86	1.95	47	49	0	0	0	6	1.90	
1.94	2.03	49	51	1	0	0	6		2.00

## LONG LATCH REQUIRED

OUTER Ø RANGE				LINK TYPE				PIPE OD	TUBE OD
MIN (in)	MAX (in)	MIN (mm)	MAX (mm)	SHORT	MEDIUM	LONG	WHEEL	(in)	(in)
2.01	2.15	51	55	0	1	0	5		
2.14	2.28	54	58	1	2	0	4		2.25
2.27	2.41	58	61	0	3	0	4	2.38	
2.38	2.52	61	64	0	2	0	6		2.50
2.51	2.64	64	67	1	3	0	5		2.50
2.64	2.77	67	70	0	4	0	5		
2.76	2.89	70	73	0	1	2	4	2.88	
2.88	3.01	73	76	0	3	1	5	2.88	
2.99	3.12	76	79	0	0	3	4		3.00
3.11	3.24	79	82	0	2	2	5		
3.23	3.37	82	86	0	4	1	6		3.25
3.34	3.47	85	88	0	1	3	5		
3.47	3.60	88	91	0	3	2	6	3.50	3.50
3.57	3.70	91	94	0	0	4	5		
3.69	3.83	94	97	0	2	3	6		3.75
3.80	3.93	96	100	1	0	4	6		
3.92	4.05	100	103	0	1	4	6		
4.00	4.13	101	105	1	1	4	6	4.00	4.00
4.12	4.25	105	108	0	2	4	6		
4.19	4.32	106	110	1	2	4	6		
4.31	4.45	110	113	0	3	4	6		
4.42	4.55	112	115	1	1	5	6	4.50	4.50
4.54	4.67	115	119	0	2	5	6		

## SCANNER COMPONENTS: Key Parts

<b>A</b>	Link Mount
<b>B</b>	Irrigation Tube
<b>C</b>	Crossbar
<b>D</b>	Crossbar Clamp Screw
<b>E</b>	Wedge Separation Indicator

<b>F</b>	(WSI) Clamp Screw
<b>G</b>	Sleeve Clamp
<b>H</b>	Crossbar Retaining Screw
<b>I</b>	Encoder
<b>J</b>	Probe Holder Arms
<b>K</b>	Probe Holder Adj. Screw
<b>L</b>	Setup Tab

